

FILE 'HOME' ENTERED AT 09:06:02 ON 09 OCT 2002

=> file medline biosis caplus  
COST IN U.S. DOLLARS

SINCE FILE	TOTAL
ENTRY	SESSION
0.21	0.21

FULL ESTIMATED COST

FILE 'MEDLINE' ENTERED AT 09:06:23 ON 09 OCT 2002

FILE 'BIOSIS' ENTERED AT 09:06:23 ON 09 OCT 2002  
COPYRIGHT (C) 2002 BIOLOGICAL ABSTRACTS INC.(R)

FILE 'CAPLUS' ENTERED AT 09:06:23 ON 09 OCT 2002  
USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.  
PLEASE SEE "HELP USAGETERMS" FOR DETAILS.  
COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY (ACS)

=> s (nuclear(w)magnetic(w)resonan?)  
L1 173424 (NUCLEAR(W) MAGNETIC(W) RESONAN?)

=> s l1 and automat? (4a) assign?  
L2 87 L1 AND AUTOMAT? (4A) ASSIGN?

=> dup rem l2  
PROCESSING COMPLETED FOR L2  
L3 76 DUP REM L2 (11 DUPLICATES REMOVED)

=> d 1-76 ti

L3 ANSWER 1 OF 76 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.  
TI Semi-**automated** backbone resonance **assignments** of the  
extracellular ligand-binding domain of an ionotropic glutamate receptor.

L3 ANSWER 2 OF 76 MEDLINE DUPLICATE 1  
TI Towards structural genomics of RNA: rapid NMR resonance assignment and  
simultaneous RNA tertiary structure determination using residual dipolar  
couplings.

L3 ANSWER 3 OF 76 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.  
TI Solution structure and dynamics of melanoma inhibitory activity protein.

L3 ANSWER 4 OF 76 MEDLINE  
TI Protein NMR structure determination with **automated** NOE  
**assignment** using the new software CANDID and the torsion angle  
dynamics algorithm DYANA.

L3 ANSWER 5 OF 76 MEDLINE  
TI Self-consistent Karplus parametrization of 3J couplings depending on the  
polypeptide side-chain torsion chil.

L3 ANSWER 6 OF 76 MEDLINE  
TI Efficient identification of amino acid types for fast protein backbone  
assignments.

L3 ANSWER 7 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Automatic determination of protein backbone resonance assignments from  
triple resonance **nuclear magnetic resonance**  
data

L3 ANSWER 8 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI MUSIC, Selective Pulses, and Tuned Delays: Amino Acid Type-Selective

## 1H-15N Correlations, II

- L3 ANSWER 9 OF 76 MEDLINE  
TI Variability in **automated assignment** of NOESY spectra and three-dimensional structure determination: a test case on three small disulfide-bonded proteins.
- L3 ANSWER 10 OF 76 MEDLINE  
TI Determination of a high precision structure of a novel protein, Linum usitatissimum trypsin inhibitor (LUTI), using computer-aided assignment of NOESY cross-peaks.
- L3 ANSWER 11 OF 76 MEDLINE DUPLICATE 2  
TI Ansig for Windows: an interactive computer program for semiautomatic assignment of protein NMR spectra.
- L3 ANSWER 12 OF 76 MEDLINE  
TI Rapid fold and structure determination of the archaeal translation elongation factor lbeta from Methanobacterium thermoautotrophicum.
- L3 ANSWER 13 OF 76 MEDLINE  
TI RFAC, a program for automated NMR R-factor estimation.
- L3 ANSWER 14 OF 76 MEDLINE  
TI A tracked approach for **automated** NMR **assignments** in proteins (TATAPRO).
- L3 ANSWER 15 OF 76 MEDLINE  
TI **Automated** analysis of NMR **assignments** and structures for proteins.
- L3 ANSWER 16 OF 76 MEDLINE  
TI Solution structure of the VEGF-binding domain of Flt-1: comparison of its free and bound states.
- L3 ANSWER 17 OF 76 MEDLINE DUPLICATE 3  
TI Exploring protein interiors: the role of a buried histidine in the KH module fold.
- L3 ANSWER 18 OF 76 MEDLINE DUPLICATE 4  
TI A high quality **nuclear magnetic resonance** solution structure of peptide deformylase from Escherichia coli: application of an **automated assignment** strategy using GARANT.
- L3 ANSWER 19 OF 76 MEDLINE DUPLICATE 5  
TI New features and enhancements in the X-PLOR computer program.
- L3 ANSWER 20 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI RESCUE: an artificial neural network tool for the NMR spectral assignment of proteins
- L3 ANSWER 21 OF 76 MEDLINE  
TI Structural characterization of an analog of the major rate-determining disulfide folding intermediate of bovine pancreatic ribonuclease A.
- L3 ANSWER 22 OF 76 MEDLINE  
TI Using neural network predicted secondary structure information in **automatic** protein NMR **assignment**.
- L3 ANSWER 23 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI **Automated** Resonance **Assignment** of Proteins Using

## Heteronuclear 3D NMR. 2. Side Chain and Sequence-Specific Assignment

- L3 ANSWER 24 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI GARANT - a general algorithm for resonance assignment of multidimensional **nuclear magnetic resonance** spectra
- L3 ANSWER 25 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Phase labeling of C-H and C-C spin-system topologies: application in constant-time PFG-CBCA(CO)NH experiments for discriminating amino acid spin-system types
- L3 ANSWER 26 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Selective identification of threonine, valine, and isoleucine sequential connectivities with a TVI-CBCACONH experiment
- L3 ANSWER 27 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI **Automated** sequence-specific NMR **assignment** of homologous proteins using the program GARANT
- L3 ANSWER 28 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Use of selective C.alpha. pulses for improvement of HN(CA)CO-D and HN(COCA)NH-D experiments
- L3 ANSWER 29 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Phase labeling of C-H and C-C spin-system topologies: application in PFG-HACANH and PFG-HACA(CO)NH triple-resonance experiments for determining backbone resonance assignments in proteins
- L3 ANSWER 30 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI A general and adaptable method for the **automated assignment** of protein multidimensional **nuclear magnetic resonance** spectra (NMR)
- L3 ANSWER 31 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Automated analysis of **nuclear magnetic resonance** assignments for proteins
- L3 ANSWER 32 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI WinDat: An NMR Database Compilation Tool, User Interface, and Spectrum Libraries for Personal Computers
- L3 ANSWER 33 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Application of structure refinement using 3D NOE-NOE spectroscopy to lac repressor headpiece (1-56)
- L3 ANSWER 34 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI AURELIA, a program for computer-aided analysis of multidimensional NMR spectra
- L3 ANSWER 35 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Computer-assisted assignment of peptides with non-standard amino acids
- L3 ANSWER 36 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Computer assignment of the backbone resonances of labeled proteins using two-dimensional correlation experiments
- L3 ANSWER 37 OF 76 MEDLINE DUPLICATE 6  
TI Protein three-dimensional structure determination and sequence-specific assignment of <sup>13</sup>C and <sup>15</sup>N-separated NOE data. A novel real-space ab initio approach.
- L3 ANSWER 38 OF 76 MEDLINE DUPLICATE 7

TI **Automated assignment** of multidimensional  
**nuclear magnetic resonance** spectra.

L3 ANSWER 39 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Computational strategies pertinent to NMR solution structure determination

L3 ANSWER 40 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Use of fuzzy mathematics for complete **automated**  
**assignment** of peptide 1H 2D NMR spectra

L3 ANSWER 41 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI A novel contour plot algorithm for the processing of 2D and 3D NMR spectra

L3 ANSWER 42 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Application of neural networks to **automated assignment**  
 of NMR spectra of proteins

L3 ANSWER 43 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Automation of protein 2D proton NMR assignment by means of fuzzy  
 mathematics and graph theory

L3 ANSWER 44 OF 76 MEDLINE  
 TI A constraint reasoning system for **automating** sequence-specific  
 resonance **assignments** from multidimensional protein NMR spectra.

L3 ANSWER 45 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Computer-assisted assignment of multidimensional NMR spectra of proteins:  
 Application to 3D NOESY-HMQC and TOCSY-HMQC spectra

L3 ANSWER 46 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI A 4D HCCH-TOCSY experiment for assigning the side chain proton and  
 carbon-13 resonances of proteins

L3 ANSWER 47 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI 4D NMR triple-resonance experiments for assignment of protein backbone  
 nuclei using shared constant-time evolution periods

L3 ANSWER 48 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI RUBIDIUM, a program for computer-aided assignment of two-dimensional NMR  
 spectra of polypeptides

L3 ANSWER 49 OF 76 MEDLINE DUPLICATE 8  
 TI Comparison of solution structures of mutant bovine pancreatic trypsin  
 inhibitor proteins using two-dimensional **nuclear**  
**magnetic resonance**.

L3 ANSWER 50 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Two- and three-dimensional proton NMR studies of apo-neocarzinostatin

L3 ANSWER 51 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Assignment of protein NMR spectra in the light of homonuclear 3D  
 spectroscopy: an automatable procedure based on 3D TOCSY-TOCSY and 3D  
 TOCSY-NOESY

L3 ANSWER 52 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI STELLA and CLAIRE: a seraglio of programs for human-aided assignment of  
 2D proton NMR spectra of proteins

L3 ANSWER 53 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Assignment of the NMR spectra of homologous proteins

L3 ANSWER 54 OF 76 CAPLUS COPYRIGHT 2002 ACS

TI New interactive and **automatic** algorithms for the **assignment** of NMR spectra

L3 ANSWER 55 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Automated analysis of NMR spectra

L3 ANSWER 56 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Pepto: an expert system for **automatic** peak **assignment** of two-dimensional **nuclear magnetic resonance** spectra of proteins

L3 ANSWER 57 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI A versatile approach toward the partially automatic recognition of cross peaks in 2D proton NMR spectra

L3 ANSWER 58 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Three-dimensional TOCSY-TOCSY processing using linear prediction, as a potential technique for **automated assignment**

L3 ANSWER 59 OF 76 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.DUPLICATE  
 9  
 TI **AUTOMATED** STEREOSPECIFIC PROTON NMR **ASSIGNMENTS** AND THEIR IMPACT ON THE PRECISION OF PROTEIN STRUCTURE DETERMINATIONS IN SOLUTION.

L3 ANSWER 60 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Heteronuclear three-dimensional NMR spectroscopy. Natural abundance carbon-13 chemical shift editing of 1H-1H COSY spectra

L3 ANSWER 61 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI A computer search system for similar organic compounds in carbon-13 **nuclear magnetic resonance** data files

L3 ANSWER 62 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI A program for semi-**automatic** sequential resonance **assignments** in protein proton **nuclear magnetic resonance** spectra

L3 ANSWER 63 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Carbon-13 NMR assignments of the bases in oligodeoxynucleotides: an automated procedure using Bayesian statistics

L3 ANSWER 64 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Use of the carbon-13 NMR chemical shift/charge density linear relationship for recognition and ranking of chemical structures

L3 ANSWER 65 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI ISOLOG: a diagnosis system for origin recognition of natural products through isotope analysis

L3 ANSWER 66 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI Toward **automated assignment** of **nuclear magnetic resonance** spectra: pattern recognition in two-dimensional correlation spectra

L3 ANSWER 67 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI CSEARCH: a computer program for identification of organic compounds and fully **automated assignment** of carbon-13 **nuclear magnetic resonance** spectra

L3 ANSWER 68 OF 76 CAPLUS COPYRIGHT 2002 ACS  
 TI **Automatic assignment** of carbon-13 NMR signals based on

the Karplus-Pople equation

L3 ANSWER 69 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI **Automatic peak assignments** for in vivo phosphorus-31  
NMR spectra

L3 ANSWER 70 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Empirical additive parameter and **automatic assignment**  
of carbon-13 NMR signals of some aryl and heteroaryl groups. A new  
criterion for a linear relationship between carbon-13 chemical shifts and  
charge densities

L3 ANSWER 71 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI **Automatic assignment** of carbon-13 NMR spectra based on  
the chemical shift/charge density relationship

L3 ANSWER 72 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Computerized analytical system (ASSIGNER) for structure determination of  
organic compounds

L3 ANSWER 73 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Automatic structural elucidation by carbon-13 NMR: DARC-EPIOS method.  
Search for a discriminant chemical structure-displacement relationship

L3 ANSWER 74 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Automatic analysis of the NMR spectra of AA'BB' type compounds with the  
**automatic assignment** of spectral lines

L3 ANSWER 75 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Shift reagent spectra. The automatic determination of relative bound  
shifts and the **automatic assignment** of signals in the  
parent spectrum. Effects of concentration, temperature, and solvent on  
relative bound shifts

L3 ANSWER 76 OF 76 CAPLUS COPYRIGHT 2002 ACS  
TI Computer program for automatic interpretation of NMR spectra on the basis  
of dipolar lanthanide shifts

=> d 44 bib ab

L3 ANSWER 44 OF 76 MEDLINE  
AN 96038996 MEDLINE  
DN 96038996 PubMed ID: 7584369  
TI A constraint reasoning system for **automating** sequence-specific  
resonance **assignments** from multidimensional protein NMR spectra.  
AU Zimmerman D E; Kulikowski C A; Montelione G T  
CS Department of Computer Science, Rutgers University, Piscataway, NJ 08854,  
USA.  
NC GM-08339 (NIGMS)  
GM-47014 (NIGMS)  
SO ISMB, (1993) 1 447-55.  
Journal code: 9509125.  
CY United States  
DT Journal; Article; (JOURNAL ARTICLE)  
LA English  
FS Priority Journals  
EM 199512  
ED Entered STN: 19960124  
Last Updated on STN: 19960124  
Entered Medline: 19951205  
AB AUTOASSIGN is a prototype expert system designed to aid in the

determination of protein structure from **nuclear magnetic resonance** (NMR) measurements. In this paper we focus on one of the key steps of this process, the assignment of the observed NMR signals to specific atomic nuclei in the protein; i.e. the determination of sequence-specific resonance assignments. Recently developed triple-resonance (<sup>1</sup>H, <sup>15</sup>N, and <sup>13</sup>C) NMR experiments [Montelione et al., 1992] have provided an important breakthrough in this field, as the resulting data are more amenable to automated analysis than data sets generated using conventional strategies [Wuethrich, 1986]. The "assignment problem" can be stated as a constraint satisfaction problem (CSP) with some added complexities. There is very little internal structure to the problem, making it difficult to apply subgoaling and problem decomposition. Moreover, the data used to generate the constraints are incomplete, non-unique, and noisy, and constraints emerge dynamically as analysis progresses. The traditional inference engine is replaced by a set of very tightly-coupled modules which enforce extensive constraint propagation, with state information distributed over the objects whose relationships are being constrained. AUTOASSIGN provides correct and nearly complete resonance assignments with both simulated and real 3D triple-resonance data for a 72 amino acid protein.

=> d 38 bib ab

L3 ANSWER 38 OF 76 MEDLINE DUPLICATE 7  
 AN 95131767 MEDLINE  
 DN 95131767 PubMed ID: 7830588  
 TI **Automated assignment** of multidimensional  
**nuclear magnetic resonance** spectra.  
 AU Oschkinat H; Croft D  
 CS European Molecular Biology Laboratory, Germany.  
 SO METHODS IN ENZYMOLOGY, (1994) 239 308-18. Ref: 41  
 Journal code: 0212271. ISSN: 0076-6879.  
 CY United States  
 DT Journal; Article; (JOURNAL ARTICLE)  
 General Review; (REVIEW)  
 (REVIEW, TUTORIAL)  
 LA English  
 FS Priority Journals  
 EM 199502  
 ED Entered STN: 19950307  
 Last Updated on STN: 19950307  
 Entered Medline: 19950217

=> d 15 bib ab

L3 ANSWER 15 OF 76 MEDLINE  
 AN 1999439930 MEDLINE  
 DN 99439930 PubMed ID: 10508776  
 TI **Automated analysis** of NMR **assignments** and structures  
 for proteins.  
 AU Moseley H N; Montelione G T  
 CS Center for Advanced Biotechnology and Medicine Department of Molecular  
 Biology and Biochemistry, Rutgers University, Piscataway, New Jersey,  
 08854-5638, USA.. hunter@cabm.rutgers.edu  
 NC GM-47014 (NIGMS)  
 SO CURRENT OPINION IN STRUCTURAL BIOLOGY, (1999 Oct) 9 (5) 635-42. Ref: 42  
 Journal code: 9107784. ISSN: 0959-440X.  
 CY ENGLAND: United Kingdom  
 DT Journal; Article; (JOURNAL ARTICLE)  
 General Review; (REVIEW)

(REVIEW, TUTORIAL)

LA English  
FS Priority Journals  
EM 199911  
ED Entered STN: 20000111  
Last Updated on STN: 20000111  
Entered Medline: 19991105  
AB Recent developments in protein NMR technology have provided spectral data that are highly amenable to analysis by advanced computer software systems. Specific data collection strategies, coupled with these computer programs, allow automated analysis of extensive backbone and sidechain resonance assignments and three-dimensional structures for proteins of 50 to 200 amino acids.

=> d 18 bib ab

L3 ANSWER 18 OF 76 MEDLINE DUPLICATE 4  
AN 1999281460 MEDLINE  
DN 99281460 PubMed ID: 10353194  
TI A high quality **nuclear magnetic resonance** solution structure of peptide deformylase from Escherichia coli: application of an **automated assignment** strategy using GARANT.  
AU O'Connell J F; Pryor K D; Grant S K; Leiting B  
CS Department of Biochemistry, Merck Research Laboratories, Rahway, NJ 07065, USA.. oconnell@merck.com  
SO JOURNAL OF BIOMOLECULAR NMR, (1999 Apr) 13 (4) 311-24.  
Journal code: 9110829. ISSN: 0925-2738.  
CY Netherlands  
DT Journal; Article; (JOURNAL ARTICLE)  
LA English  
FS Priority Journals  
EM 199906  
ED Entered STN: 19990712  
Last Updated on STN: 20000303  
Entered Medline: 19990624  
AB The NMR structure of the peptide deformylase (PDF) (1-150) from Escherichia coli, which is an essential enzyme that removes the formyl group from nascent polypeptides and represents a potential target for drug discovery, was determined using 15N/13C doubly labeled protein. Nearly completely **automated assignment** routines were employed to assign three-dimensional triple resonance, 15N-resolved and 13C-resolved NOESY spectra using the program GARANT. This assignment strategy, demonstrated on a 17 kDa protein, is a significant advance in the **automation** of NMR data **assignment** and structure determination that will accelerate future work. A total of 2302 conformational constraints were collected as input for the distance geometry program DYANA. After restrained energy minimization with the program X-PLOR the 20 best conformers characterize a high quality structure with an average of 0.43 A for the root-mean-square deviation calculated from the backbone atoms N, C alpha and C', and 0.81 A for all heavy atoms of the individual conformers relative to the mean coordinates for residues 1 to 150. The globular fold of PDF contains two alpha-helices comprising residues 25-40, 125-138, six beta-strands 57-60, 70-77, 85-88, 98-101, 105-111, 117-123 and one 3(10) helix comprising residues 49-51. The C-terminal helix contains the HEXXH motif positioning a zinc ligand in a similar fashion to other metalloproteases, with the third ligand being cysteine and the fourth presumably a water. The three-dimensional structure of PDF affords insight into the substrate recognition and specificity for N-formylated over N-acetylated substrates and is compared to other PDF structures.



=> d 24, 27, 30, 31 bib ab

L3 ANSWER 24 OF 76 CAPLUS COPYRIGHT 2002 ACS  
AN 1997:10368 CAPLUS  
DN 126:138925  
TI GARANT - a general algorithm for resonance assignment of multidimensional  
**nuclear magnetic resonance** spectra  
AU Bartels, Christian; Guentert, Peter; Billeter, Martin; Wuethrich, Kurt  
CS Institut Molekularbiologie Biophysik, Eidgenoessische Technische  
Hochschule-Hoenggerberg, Zurich, CH-8093, Switz.  
SO Journal of Computational Chemistry (1997), 18(1), 139-149  
CODEN: JCCHDD; ISSN: 0192-8651  
PB Wiley  
DT Journal  
LA English  
AB A new program for **automatic** resonance **assignment** of  
NMR spectra of proteins, GARANT (General Algorithm for Resonance  
Assignment), is introduced. Three principal elements used in this approach  
are: (a) representation of resonance assignments as an optimal match of  
two graphs describing, resp., peaks expected from combined knowledge of  
the primary structure and the magnetization transfer pathways in the  
spectra used, and exptl. obsd. peaks; (b) a scoring scheme able to  
distinguish between correct and incorrect resonance assignments; and (c)  
combination of an evolutionary algorithm with a local optimization  
routine. The score that evaluates the match of expected peaks to obsd.  
relies on the agreement of the information available about these peaks,  
most prominently, but not exclusively, the chem. shifts. Tests show that  
the combination of an evolutionary algorithm and a local optimization  
routinely results that are clearly superior to those obtained when using  
either of the two techniques sep. in the search for the correct  
assignments. GARANT is laid out for assignment problems involving peaks  
obsd. in two- and three-dimensional homonuclear and heteronuclear NMR  
spectra of proteins.

L3 ANSWER 27 OF 76 CAPLUS COPYRIGHT 2002 ACS  
AN 1996:408828 CAPLUS  
DN 125:137103  
TI **Automated** sequence-specific NMR **assignment** of  
homologous proteins using the program GARANT  
AU Bartels, Christian; Billeter, Martin; Guentert, Peter; Wuethrich, Kurt  
CS Inst. Mol. Biophysik, Eidgenoessische Technische Hochschule-Hoenggerberg,  
Zurich, CH-8093, Switz.  
SO Journal of Biomolecular NMR (1996), 7(3), 207-213  
CODEN: JBNME9; ISSN: 0925-2738  
PB ESCOM  
DT Journal  
LA English  
AB The program GRANT (General Algorithm for Resonance **Assignment**)  
for **automated** sequence-specific NMR **assignment** of  
proteins is based on the mapping of peaks predicted from the amino acid  
sequence onto the peaks obsd. in multidimensional spectra (1996). In this  
paper we demonstrate the potential of GARANT for the assignment of  
homologous proteins when either the three-dimensional structure or the  
chem. shifts of the parent protein are known. In these applications,  
GARANT utilizes supplementary information either in the form of interat.  
distances derived from the three-dimensional structure, to add nuclear  
Overhauser effects reflecting the tertiary structure to the list of  
expected peaks, or in the form of the chem. shifts of the parent protein,  
to obtain a better est. of the positions of the expected peaks. The  
procedure is illustrated with three different proteins: (i) a mutant form

of Tendamistat (74 residues), using homonuclear 2D 1H NMR spectra and either the three-dimensional structure or the chem. shifts of the wild-type protein; (ii) the mutant Antp(C39S,W56S) homeodomain (68 residues), using homonuclear 2D 1H NMR spectra and the three-dimensional structure of the Antp(C39S) homeodomain; and (iii) free cyclophilin A (165 residues), using heteronuclear 3D NMR spectra and the three-dimensional structure of a cyclophilin A-cyclosporin A complex. In these three systems nearly complete assignment of the polypeptide backbone resonances and assignment of over 80% of the amino acid side-chain resonances was obtained without manual intervention.

L3 ANSWER 30 OF 76 CAPLUS COPYRIGHT 2002 ACS

AN 1996:408812 CAPLUS

DN 125:77742

TI A general and adaptable method for the **automated assignment** of protein multidimensional **nuclear magnetic resonance** spectra (NMR)

AU Olson, John Bernard, Jr.

CS Univ. of Wisconsin, Madison, WI, USA

SO (1995) 216 pp. Avail.: Univ. Microfilms Int., Order No. DA9608152

From: Diss. Abstr. Int., B 1996, 57(1), 309

DT Dissertation

LA English

AB Unavailable

L3 ANSWER 31 OF 76 CAPLUS COPYRIGHT 2002 ACS

AN 1995:911855 CAPLUS

DN 123:309747

TI Automated analysis of **nuclear magnetic resonance** assignments for proteins

AU Zimmerman, Diane E.; Montelione, Gaetano T.

CS Rutgers Univ., Piscataway, NJ, USA

SO Current Opinion in Structural Biology (1995), 5(5), 664-73

CODEN: COSBEF; ISSN: 0959-440X

PB Current Biology

DT Journal

LA English

AB Recent developments in protein NMR technol. provide spectral data that are highly amenable to anal. by computer software systems. Automated methods of anal. use constraint satisfaction, pseudoenergy minimization, directed search, neural net, simulated annealing, and/or genetic algorithms to establish sequential links and sequence-specific assignments. The most advanced systems provide automated anal. of complete backbone and extensive side-chain resonance assignments for proteins of 50-150 amino acids.

=> FIL STNGUIDE

COST IN U.S. DOLLARS

SINCE FILE	TOTAL
ENTRY	SESSION

FULL ESTIMATED COST

38.20	38.41
-------	-------

DISCOUNT AMOUNTS (FOR QUALIFYING ACCOUNTS)

SINCE FILE	TOTAL
ENTRY	SESSION

CA SUBSCRIBER PRICE

-1.86	-1.86
-------	-------

FILE 'STNGUIDE' ENTERED AT 09:14:24 ON 09 OCT 2002

USE IS SUBJECT TO THE TERMS OF YOUR CUSTOMER AGREEMENT

COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY, JAPAN SCIENCE

AND TECHNOLOGY CORPORATION, AND FACHINFORMATIONSZENTRUM KARLSRUHE